



BATTERIA

BASSO VOLTAGGIO

WALL MOUNTED

ES-BOX12-5.12KWH

ES-BOX12 PLUS-10KWH



CARATTERISTICHE



Energia specifica
più alta



Facile
Installazione



8000 Cicli di carica e
scarica



BMS intelligente per
ottimizzare la resa
energetica



Modulabile fino a 15
batterie in parallelo



Protezione dell'ambiente
e nessun inquinamento

CARATTERISTICHE	ES-BOX12-5.12KWH	ES-BOX12 PLUS-10KWH
Product Specificaton	51.2V 100Ah	51.2V 200Ah
Nominal Voltage	51.2V	51.2V
Nominal Capacity	100Ah	202Ah
Cell Type	(LFP)	(LFP)
Standard Charge Voltage	58.4V(adjustable)	58.4V(adjustable)
Max Charge Current	100A	150A
Discharge Cut-Off Voltage	40V(adjustable)	40V(adjustable)
Max Discharge Current	100A	150A
Display	LED	LED
Parallel Function	Support 10 Units In Parallel	Support 15 Units In Parallel
Communication Interface	RS485-RS232	RS485-RS232
Cycle Life *	≥8000 Cycles (80%DOD)	≥8000 Cycles (80%DOD)
Charge Temperature Range	0~65°C	0~65°C
Discharge Temperature Range	-20~65°C	-20~65°C
Dimensions	480*600*150MM	480*650*225MM
Weight	47Kg	93Kg
Installation Method	Wall Mounted / Stand	Wall Mounted / Stand
Enclosure Protect Level	IP22	IP22

CLASSE A+

